

Straight connection joint-PP



Low voltage 0,6/1 (1,2) kV, Telecommunication and Signalisation
Inside / outside underground, above ground, underwater, in cable ducts
Snaplock shells made of polypropylene, easy to cut to length.

Features

- Type tested according to: EN 50393:2006-11
- Hydrolysis resistant polyurethane resin in transparent 2-component bag
- Snaplock shells made of polypropylene, easy to cut to length.
- Fully waterproof, no leakage of liquid resin
- Complete kit, sealing tape, sandpaper, and protective gloves inclusive
- Installation instruction with clear drawings
- Easy and quick installation
- Connectors and/or earthing kits available on request
- Other shell size dimensions available on request

More info

[Download: Mixing instructions](#)

Straight connection joint-PP



Products

Art.nr.	Product Name	Cable diameter (mm)	Dimensions (mm)	Order unit
88000950	Straight connection joint PP 4x4mm ²	Ø 07 - 16	180x25	per piece
88000951	Straight connection joint PP 4x16mm ²	Ø 08 - 25	216x38	per piece
88000952	Straight connection joint PP 4x25mm ²	Ø 14 - 30	275x48	per piece
88000953	Straight connection joint PP 4x50mm ²	Ø 23 - 36	360x55	per piece