

Straight connection joint telecom and signalisation



Cast resin joint for telecommunication and signalisation
Inside / outside underground, above ground, underwater, in cable ducts

Features

- Hydrolysis resistant polyurethane resin in transparent 2-component bag
- Strong transparent snaplock shells
- Fully waterproof, no leakage of liquid resin
- Complete kit, sealing tape, sandpaper, and protective gloves inclusive
- Installation instruction with clear drawings
- Easy and quick installation
- Connectors and/or earthing kits available on request
- Other shell size dimensions available on request

Specifications

Art.nr.	Cable diameter (mm)	Number of conductors	Dimensions (mm)
80163	6 - 28	10 x 1,5mm ²	189 x 40
80164	12 - 32	60 x 1,5mm ²	275 x 50
80165	26 - 53	100 x 1,5mm ²	355 x 72

Straight connection joint telecom and signalisation

Products

Art.nr.	Product Name	Cable diameter (mm)	Dimensions (mm)	Order unit
80163	Straight connection joint till 4x6mm ²	Ø 06 - 28	L189 x Ø40	per piece
80164	Straight connection joint till 4x16mm ²	Ø 12 - 32	L250 x Ø45	per piece
80165	Straight connection joint till 4x50mm ²	Ø 26 - 53	L355 x Ø72	per piece
8.000907	Straight connection joint till 4x95mm ²	Ø 30 - 48	L450 x Ø75	per piece