

Sealing plugs




Filoform sealing plugs have been developed to provide an effective and simple solution to all splash water and dirt tight sealing requirements in HDPE ducts, protective sleeves and diamond-drilled ducts.

The sealing plugs are standard dirt and splash watertight. After mounting with sealing compound Filoform Fill & Seal (art.nr. 80840) the Filoform sealing plugs easily exceed a gas- and watertight sealing of 0.2 bar.

The Filoform sealing plugs are made from a high quality TPE, this material has a hardness of 40 Shore A.

Features

- Formed from one part
- Easy to install
- Durable sealing
- made from high quality TPE



Specifications

- Material : TPE
- Hardness : 40 Shore A

Products

Art.nr.	Product Name	Maximum cable or pipe diameter in the duct (mm)	Outside diameter HDPE duct (mm)	Duct diameter min.-max. (mm)	Order unit
43200	Plug 25/20mm - 7mm	7	25	20	300 pcs/carton
822620	Plug 25/20mm - 7mm with slit	7	25	20	300 pcs/carton
43202	Plug 25/20mm - 10,5mm	10,5	25	20	300 pcs/carton
822614	Plug 40/33mm - 4x12mm	4x12mm	40	33	On request
822503	Plug 50/43,6mm - 7mm	7	50	43,6	50 pcs/carton
822504	Plug 50/43,6mm - 10,5mm	10,5	50	43,6	50 pcs/carton
822502	Plug 50/43,6mm - 14mm	14	50	43,6	50 pcs/carton
822501	Plug 50/43,6mm - 25mm	25	50	43,6	25 pcs/carton
822501D	Plug 50/43,6mm-25mm Divisible	25	50	43,6	25 pcs/carton
82222	Plug 58/50mm - 32mm	32	58	50	15 pcs/carton