

# Divisible duct seals 10mm



Filoform divisible duct sealing sets for subducts have been developed to provide an effective and simple solution to all Gas and Watertight duct sealing requirements.

This modular system enables you to install it easily onto new and existing installations. Due to the compact design the seals can be installed in all situations, even in locations with difficult access.

For use on subducts of 10mm.


PATENTED

## Features

- Gas and Watertight up to 0,5 bar.
- Suitable for retrofitting.
- Easy installation.
- Slim design.
- Other versions available upon request.

# Divisible duct seals 10mm

## Specifications



Dimensions	A (mm)	B (mm)	Weight (gr.)
Duct seal 10mm	30	24	12

## Material specification

Properties	Value
Plastic scales	glassfibre reinforced
Cutting block	glassfibre reinforced
Sealing plug	silicone
Sealing	up to 0,5 bar
Pull-out force duct seal vs duct	≥ 100N
Mechanical compression strength	≥ 1000N, 10 sec.

# Divisible duct seals 10mm

## More info

### Contents

- 2 pieces of plastic shells with click together fixings
- 1 piece cutting block
- 1 rubber seal
- Illustrated installation instructions

Deelbare glasvezel afdichting  
Divisible fibre optic seals  
Teilbar LWL-dichtungen  
Fibre optique divisible sceaux  
Sellos de fibra optica

**FILO**form



# Divisible duct seals 10mm

## Products

Art.nr.	Product Name	Colour	Duct outside diameter (mm)	Cable Diameter (mm)	Order unit
822810.0	Duct seal 10mm / 2,5-1,5mm	purple	10	2,5-1,5	25 pcs/carton
822810.1	Duct seal 10mm / 3,5-2,5mm	light blue	10	3,5-2,5	25 pcs/carton
822810.2	Duct seal 10mm / 5,0-3,5mm	green	10	5,0-3,5	25 pcs/carton
822810.3	Duct seal 10mm / 6,5-5,0mm	red	10	6,5-5,0	25 pcs/carton
822810.4	Duct seal 10mm / 7,5-6,5mm	dark blue	10	7,5-6,5	25 pcs/carton